-continued

Asn	Thr	Lys	Val	Asp 215	Lys	Lys	Val	Glu	Pro 220	Lys	Ser	Cys	Asp	L y s 225
Thr	His	Thr	Cys	Pro 230	Pro	Cys	Pro	Ala	Pro 235	Glu	Leu	Leu	Gly	Gly 240
Pro	Ser	Val	Phe	Leu 245	Phe	Pro	Pro	Lys	Pro 250	Lys	Asp	Thr	Leu	Met 255
Ile	Ser	Arg	Thr	Pro 260	Glu	Val	Thr	Суѕ	Val 265	Val	Val	Asp	Val	Ser 270
His	Glu	Asp	Pro	Glu 275	Val	Lys	Phe	Asn	Trp 280	Tyr	Val	Asp	Gly	Val 285
Glu	Val	His	Asn	Ala 290	Lys	Thr	Lys	Pro	Arg 295	Glu	Glu	Gln	Tyr	Asn 300
Ser	Thr	Tyr	Arg	Val 305	Val	Ser	Val	Leu	Thr 310	Val	Leu	His	Gln	Asp 315
Trp	Leu	Asn	Gly	Lys 320	Glu	Tyr	Lys	Cys	Lys 325	Val	Ser	Asn	Lys	Ala 330
Leu	Pro	Ala	Pro	Ile 335	Glu	Lys	Thr	Ile	Ser 340	Lys	Ala	Lys	Gly	Gln 345
Pro	Arg	Glu	Pro	Gln 350	Val	Tyr	Thr	Leu	Pro 355	Pro	Ser	Arg	Glu	Glu 360
Met	Thr	Lys	Asn	Gln 365	Val	Ser	Leu	Thr	C y s 370	Leu	Val	Lys	Gly	Phe 375
Tyr	Pro	Ser	Asp	Ile 380	Ala	Val	Glu	Trp	Glu 385	Ser	Asn	Gly	Gln	Pro 390
Glu	Asn	Asn	Tyr	Lys 395	Thr	Thr	Pro	Pro	Val 400	Leu	Asp	Ser	Asp	Gly 405
Ser	Phe	Phe	Leu	Tyr 410	Ser	Lys	Leu	Thr	Val 415	Asp	Lys	Ser	Arg	Trp 420
Gln	Gln	Gly	Asn	Val 425	Phe	Ser	Cys	Ser	Val 430	Met	His	Glu	Ala	Leu 435
His	Asn	His	Tyr	Thr 440	Gln	Lys	Ser	Leu	Ser 445	Leu	Ser	Pro	Gly	

What is claimed is:

- 1. A method for purifying a polypeptide from a composition comprising the polypeptide and a deamidated variant thereof, which method comprises the following steps performed sequentially:
 - (a) binding the polypeptide and deamidated variant to an ion exchange material using a loading buffer, wherein the loading buffer is at a first conductivity and pH;
 - (b) washing the ion exchange material with an intermediate buffer at a second conductivity and/or pH so as to elute the deamidated variant from the ion exchange material;
 - (c) washing the ion exchange material with a wash buffer which is at a third conductivity and/or pH, wherein the change in conductivity and/or pH from the intermediate buffer to the wash buffer is in an opposite
 - direction to the change in conductivity and/or pH from the loading buffer to the intersediate buffer; and
 - (d) washing the ion exchange material with an elution buffer at a fourth conductivity and/or pH so as to elute the polypeptide from the ion exchange material.
- 2. The method of claim 1 wherein the ion exchange material comprises a cation exchange resin.

- 3. The method of claim 2 wherein the conductivity and/or pH of the intermediate buffer is/are greater than the conductivity and/or pH of the loading buffer and the conductivity and/or pH of the wash buffer is/are less than the conductivity and/or pH of the intermediate buffer.
- 4. The method of claim 2 wherein the conductivity and/or pH of the elution, buffer is/are greater than the conductivity and/or pH of the intermediate buffer.
- 5. The method of claim 2 wherein the cation exchange resin comprises sulphopropyl immobilized on agarose.
- 6. The method of claim 1 wherein the ion exchange 55 material comprises an anion exchange resin.
 - 7. The method of claim 1 wherein the conductivity and/or pH of the wash buffer is/are about the same as the conductivity and/or pH of the loading buffer.
- 8. The method of claim 1 wherein elution of the deami-60 dated variant and of the polypeptide is achieved by modifying the conductivity of the intermediate buffer and of the elution buffer, respectively.
 - 9. The method of claim 8 herein the pH remains approximately constant for each of steps (a)–(d).
 - 10. The method of claim 8 wherein the conductivity of the intermediate buffer and of the elution buffer is modified by changing the salt concentration therein.